

```

/*
A Program to Convert Wordstar word processor files (versions 3/4/5/7) to HTML format.
original version Apr 13, 1999
major revision and expansion v. 7, July 13, 2019

syntax is: WS_HTM directory

where directory is a filespec
-----
environment: Linux
-----
This program is in the public domain, and may be
used for any purpose whatsoever, without permission
or notification, but it is offered "as-is" without
any warrentee, express or implied.
-----
This is not debugged code. It is published as a interim measure in case my
health should prevent me from completing it

For Ayantu and Dayanna, Daughters of my Heart

Andrew D. Todd
1249 Pineview Dr., Apt 1
Morgantown, WV 26505

*/
#include <stdlib.h>
#include <string.h>
#include <stdio.h>
#include <io.h>
#include <fcntl.h>
#include <sys\types.h>
#include <sys\stat.h>
#include <dirent.h>
-----*/

struct file_table_type
{
char old_filename_ext[32];
char old_f_spec[256];
char new_f_spec[256];
char new_title[256];
}
table_of_old_files[1600];
/*
Wordstar 3 did not support directories internally.
Consequently, huge numbers of files might wind up
being placed in a single directory on a hard drive,
named in a logical fashion, eg.two letters for the book,
two numerals for the chapter, and one letter for
the version.The wordstar program files would go
in the same directory. The user would just make
that directory the default directory, and proceed
as if the rest of the hard drive did not exist.
1600 files seems a prudent allocation.
*/
main(int argc, char *argv[])
{
int num_files;
char dir_spec[256];
/*get the directory name*/
if( argc < 2 )
{
printf(" \nDirectory Name Needed\n");
_exit(3);
}
strcpy(&dir_spec, argv[1]);
/*
Read in all the directory entries for this path,
and put them in an array of directory entries
*/
num_files = make_a_table_of_old_files(&dir_spec,table_of_old_files);
/* And add the titles */
add_titles_to_table(dir_spec,table_of_old_files,num_files);
/* And sort them in order of relevance */
qsort(
table_of_old_files,
num_files,
sizeof(struct file_table_type),
cmp_final_order
);
if((argc >= 3)&&(strcmp(argv[2], "j") == 0))
process_joined_wordstar_files(
dir_spec, table_of_old_files, num_files);
else
process_wordstar_files(dir_spec,table_of_old_files, num_files);
_exit(0);
}

-----*/
int cmp_final_order(void *name_and_ext1, void *name_and_ext2)
{
int class1 = find_priority_class(name_and_ext1);
int class2 = find_priority_class(name_and_ext2);
if(class1 != class2) return(class1-class2);
else if( (class1 == 1) || (class1 == 3) )
return(strcmpi(name_and_ext1, name_and_ext2));
else if( class = 2 )
{
if(
non_ws_ext_ret= strcmpi(
file_ext_of_name_and_ext(name_and_ext1),
file_ext_of_name_and_ext(name_and_ext1)
)
!= 0
)return(non_ws_ext_ret);
else return(strcmpi(name_and_ext1, name_and_ext2));
}
}
Sort as: WordStar, non-WordStar, WordStar backup
For primary Wordstar file,
sort by case independent filename and extension.
For backup files, sort by filename
For non-wordstar files,
sort by case independent extension,
and then by case independent filename
*/
-----*/
int find_priority_class(char *arg)
{
char *file_ext = file_ext_of_name_and_ext(arg);
if(is_not_wordstar_file_extension(file_ext))
return(2);
else if( strcmpi(file_ext, "bak")== 0) return(3);
else return(1);
}
/*
returns 1 for a primary wordstar file,
3 for a backup,
and 2 for something which is not a wordstar document
*/
-----*/
char *pf_title_of_directory(char *title, char *dir_spec)
{
char directory[256];
if(directory_of_filespec(&directory, dir_spec) == NULL) return(NULL);
if(file_name_and_ext_of_filespec(dir_spec) == NULL) return(NULL);
if( get_title_for_fn_ext(
title,
directory_of_filespec(&directory, dir_spec)
file_name_and_ext_of_filespec(dir_spec)
) == NULL;) return(NULL);
else return(title);
}
/*
Returns a title for thr directory,
from a profinder file in the enclosing directory,
if possible, otherwise returns NULL
*/

```

```

/*-----*/
int make_a_table_of_old_files(
    char *dir_name,
    struct
        file_table_type
        table_of_old_files[]
    )
{
    int i, num_files;
    struct dirent *dir_entry;
    struct stat *stat_buffer;
    DIR *dr = opendir(dir_name);
    i=0;
    while( dir_entry = readdir(dr) != NULL)
        if(dir_entry -> d_type == DT_REG)
            {
                strcpy(table_of_old_files[i]->old_f_spec,
                    dir_entry->d_name);
                stat(dir_entry->d_name, stat_buffer);
                file_name_and_ext_of_filespec(
                    table_of_old_files[i]->old_filename_ext,
                    dir_entry->d_name
                );
                html_filespec_from_old_filespec(
                    table_of_old_files[i]->new_f_spec,
                    dir_entry->d_name
                );
                build_initial_title_line(
                    table_of_old_files[i]->new_title,
                    table_of_old_files[i]->old_filename_ext,
                    stat_buffer->st_size,
                    stat_buffer->st_mtim
                );
                i++;
            }
    num_files=i;
    closedir(dr);
    return(num_files)
}
/*
read in all the entries for this directory,
and put those that are ordinary files
into an array of directory entries,
together with their time/date stamps and sizes,
and original and new names,
and return the number of such files
*/

```

```

/*-----*/
int add_titles_to_table(
    char *dir_name,
    struct
        file_table_type
        table_of_old_files[],
    int num_files
    )
{
    char *comma_ptr, *title_file_title, *title_file_fn_ext;
    char new_line[200], titles_pf_file_spec[256];
    FILE *fp;
    qsort(
        table_of_old_files,
        num_files,
        sizeof(struct file_table_type),
        strcmpi
    );
    /*get in the TITLES.PF file*/
    strcpy(titles_pf_file_spec, dir_name);
    strcat(titles_pf_file_spec, "/TITLES.PF");
    if(fp=fopen(titles_pf_file_spec, "r") == NULL) return(0);
    for(;;)
        {
            if(fggets(new_line, 200, fp) == NULL) break;
            else
                {
                    /*and merge each title to the appropriate file record*/
                    if(comma_ptr=strchr(new_line, ',') != NULL)
                        {
                            title_file_title=comma_ptr+1;
                            title_file_fn_ext=new_line;
                            *comma_ptr='\0';
                            if(
                                address_of_match =
                                    bsearch(
                                        title_file_fn_ext,
                                        table_of_old_files,
                                        num_files,
                                        sizeof(struct file_table_type),
                                        strcmpi
                                    )
                                != NULL)
                                strcat(
                                    table_of_old_files[
                                        record_address_to_index(
                                            address_of_match,
                                            table_of_old_files,
                                            sizeof(struct file_table_type)
                                        )]-> new_title,
                                    title_file_title
                                );
                        }
                }
            fclose(fp);
            return(1)
        }
}
/*
ancestral MS-DOS only supported 8-character file names,
and 3-character file type extensions. Like many other
contemporary applications, additional information
was placed in a titles file, maintained by the
auxiliary application, Profinder. For purposes
of matching up records, ignore case, which is
not significant in MS-DOS filenames.
*/

```

```

/*-----*/
char *get_title_for_fn_ext(
    char *title,
    char *dir_name,
    char *fn_ext
)
{
    char *comma_ptr, *title_file_title, *title_file_fn_ext;
    char new_line[200], titles_pf_file_spec[256];
    FILE *fp;
    /*get in the TITLES.PF file*/
    strcpy(titles_pf_file_spec, dir_name);
    strcat(titles_pf_file_spec, "/TITLES.PF");
    if(fp=fopen(titles_pf_file_spec, "r") == NULL)
        for(;;)
        {
            if(fgets(new_line, 200, fp) == NULL)
            {
                fclose(fp);
                return(NULL);
            }
            else
            {
                /**/
                if(comma_ptr=strchr(new_line, ',') != NULL)
                {
                    title=comma_ptr+1;
                    if(strncmp(fn_ext, title) == 0)
                    {
                        fclose(fp);
                        return(title);
                    }
                }
            }
        }
    fclose(fp);
    return(NULL);
}
/*
Same remarks as "add_titles_to_table," only this is for retrieving a
single title.
*/
/*-----*/
record_address_to_index(
    address_of_record,
    address_of_array,
    size_of_record
)
{
    return(address_of_record-address_of_array)/size_of_record;
}
/*-----*/
build_initial_title_line(
    char *new_title,
    char *old_filename_ext,
    off_t st_size,
    struct timespec st_mtim
)
{
    char date_str[32];
    ctime_r(st_mtim, &date_str);
    sprintf(new_title, "%s %s %u ", old_filename_ext, &date_str, st_size );
}
/*-----*/
char *file_name_and_ext_of_filespec(char *filespec)
{
    char *slash_loc;
    if(filespec == NULL) return(NULL);
    else if(filespec[0] == '\0') return(NULL);
    else if(filespec[strlen(filespec)-1] == '/') return(NULL);
    else if(
        slash_loc = strrchr(filespec, '/')
        != NULL
    ) return(slash_loc+1);
    else return(filespec);
}
/*
If the argument is NULL, or the string is empty, return NULL
If the last character is a slash, return NULL.
Otherwise return whatever is after the last slash.
If no slash found, return the whole string.
*/

```

```

/*-----*/
char *directory_of_filespec(char *path, char *filespec)
{
    char *slash_loc;
    if(filespec == NULL) return(NULL);
    else if(filespec[0] == '\0') return(NULL);
    else
    {
        strcpy(path, filespec);
        if(
            slash_loc = strrchr(path, '/')
            == NULL
        )
            return(NULL);
        else
        {
            *slash_loc='\0';
            return(path);
        }
    }
}
/*
If the argument is NULL, or the string is empty, return NULL
Else if no slash found, return NULL.
Otherwise return whatever is up to
the last slash.
*/
/*-----*/
char *file_ext_of_name_and_ext(char *name_and_ext)
{
    char *last_period_loc;
    int chars_after_period;
    if(name_and_ext == NULL) return(NULL);
    else if(name_and_ext[0] == '\0') return(NULL);
    else
    {
        last_period_loc = strrchr(name_and_ext, '.');
        chars_after_period=
            name_and_ext
            +strlen(name_and_ext)
            -last_period_loc;
        if(last_period_loc == name_and_ext) return(NULL);
        else if (
            (chars_after_period <= 4)
            &&
            (chars_after_period >= 1)
        ) return(last_period_loc);
        else return(NULL);
    }
}
/*
If the argument is NULL, or the string is empty, return NULL
Otherwise find the last period,
which is not the first character,
nor more than four characters from the end,
and point to whatever is after it.
If no such period found,
or it is the last character,
return NULL
*/
/*-----*/
char *html_filespec_from_old_filespec(
    char *new_filespec,
    char *old_filespec
)
{
    char name_and_ext[32];
    char *file_extension;
    strcpy(new_filespec, old_filespec);
    if(
        file_extension= file_ext_of_name_and_ext(
            file_name_and_ext_of_filespec(
                new_filespec
            )
        ) != NULL
    )
    {
        *(file_extension-1)='_';
        strcat(new_filespec, ".html");
    }
    else strcat(new_filespec, "____.html");
    return(new_filespec);
}
/*
if the file extension is not empty,
turn the preceding period into an underscore, and
append ".html"
If it is empty, append "____.html"
*/

```

```

/*-----*/
int is_not_wordstar_file_extension(char *file_extension)
{
    char c_file_extension[10];
    if(file_extension == NULL) return(0);
    strcpy(&c_file_extension, file_extension);
    strupr(&c_file_extension);
    if(
        (strcmp(&c_file_extension, "PF") == 0)
        || (strcmp(&c_file_extension, "GIF") == 0)
        || (strcmp(&c_file_extension, "JPG") == 0)
        || (strcmp(&c_file_extension, "TXT") == 0)
        || (strcmp(&c_file_extension, "BAT") == 0)
        || (strcmp(&c_file_extension, "ASM") == 0)
        || (strcmp(&c_file_extension, "BAS") == 0)
        || (strcmp(&c_file_extension, "C") == 0)
        || (strcmp(&c_file_extension, "COM") == 0)
        || (strcmp(&c_file_extension, "EXE") == 0)
        || (strcmp(&c_file_extension, "OVR") == 0)
        || (strcmp(&c_file_extension, "INS") == 0)
        || (strcmp(&c_file_extension, "WKS") == 0)
        || (strcmp(&c_file_extension, "ZIP") == 0)
    )return(1);
    else return(0);
}
/*
Distinguish file types which are not going to be converted,
ignoring capitalization (file case is not significant in MS-DOS)

There is no uniform convention for what extension a Wordstar
file has. The program did not enforce or auto-suggest one,
the default was no extension at all, and while the manual
suggested the use of DOC, this was overtaken by Microsoft
Word's superior claims. I myself used WS3, WS5, and WS7.
Thus we can only identify things which are not Wordstar
files, and err on the side of nondestructively generating
a certain amount of garbage.

Parenthetically, WordStar had a non-document mode for editing
programs and scripts. It generated straight ASCII,
except for the file being padded out with Cntrl-Z's at the end.
It was convenient if you already knew how to use WordStar,
but it did not have the features of modern programmers'
editors, such as syntax recognition.

BUT the new table of contents file should nonetheless list files if they
have titles
*/

```

```

/*-----*/
/* Read Files and Weite Other Files */
/*-----*/
process_wordstar_files(
    char *dir_spec,
    struct
        file_table_type
        table_of_old_files[],
    int num_files
)
{
    int f_tc_out;
    int i;
    f_tc_out= open_output_html_wordstar_title_file(dir_spec);
    if( f_tc_out == -1) return(-2);
    for(i=0; i < num_files; i++)
    {
        if(
            is_not_wordstar_file_extension(
                file_ext_of_name_and_ext(
                    table_of_old_files[i]
                    ->old_filename_ext
                )
            )
        )
            make_table_of_contents_entry(
                f_tc_out,
                table_of_old_files[i]
                ->old_f_spec,
                table_of_old_files[i]
                ->new_title
            );
        else
        {
            make_table_of_contents_entry(
                f_tc_out,
                table_of_old_files[i]
                ->new_f_spec,
                table_of_old_files[i]
                ->new_title
            );
            translate_wordstar_file_to_html(
                table_of_old_files[i]
                ->old_f_spec,
                table_of_old_files[i]
                ->new_f_spec,
                table_of_old_files[i]
                ->new_title
            );
        }
    }
    /* now add the tail and close*/
    close_output_html_file(f_tc_out);
    return(1);
}
/*
Go through the table,
and convert every wordstar file,
and create an entry for every file in titles_pf.html
*/

```

```

/*-----*/
translate_wordstar_file_to_html(
    char *wordstar_file,
    char *html_file,
    char *title
)
{
    int bytes_read, f_in, f_out;
    int start_point_offset = 80000
    unsigned char input_buffer[10000000];
    f_in = open(wordstar_file, O_RDONLY|O_BINARY);
    if(f_in == -1) return(-1);
    f_out = open_output_html_file_w_title(
        html_file, title, title);
    if( f_out == -1) return(-2);
    /* read thefile into a buffer. Leave 80K vacant up front */
    bytes_read = read(
        f_in,
        (input_buffer+start_point_offset),
        (sizeof(input_buffer)-start_point_offset)
    );
    if(bytes_read <= 1) return(-3);
    parse_buffer(
        f_out,
        input_buffer,
        sizeof(input_buffer),
        start_point_offset,
        bytes_read
    );
    /* now add the tail and close*/
    close_output_html_file(int f_out);
    close(f_in);
    return(1); }
/*-----*/

process_joined_wordstar_files(
    char *dir_spec,
    struct
        file_table_type
        table_of_old_files[],
    int num_files
)
{
    int f_tc_out;
    int i;
    f_tc_out= open_output_html_wordstar_title_file(dir_spec);
    if( f_tc_out == -1) return(-2);
    for(i=0;i < num_files; i++)
    {
        if(
            is_not_wordstar_file_extension(
                file_ext_of_name_and_ext(
                    table_of_old_files[i]
                    ->old_filename_ext
                )
            )
        )
            make_table_of_contents_entry(
                f_tc_out,
                table_of_old_files[i]
                ->old_f_spec,
                table_of_old_files[i]
                ->new_title
            );
        else
            make_internal_table_of_contents_entry(f_tc_out,
                table_of_old_files[i]
                ->old_filename_ext,
                table_of_old_files[i]
                ->new_title
            );
    }
    for(i=0;i < num_files; i++)
        if(
            !is_not_wordstar_file_extension(
                file_ext_of_name_and_ext(
                    table_of_old_files[i]
                    ->old_filename_ext
                )
            )
        )
            translate_wordstar_file_to_joined_html(
                table_of_old_files[i]
                ->old_f_spec,
                f_tc_out,
                table_of_old_files[i]
                ->old_filename_ext,
                table_of_old_files[]
                ->new_title
            );
    /* now add the tail and close*/
    close_output_html_file(int f_tc_out);
    return(1);
}

```

```

/*
    Go through the table,
    and convert every wordstar file,
    and create an entry for every file in titles_pf.html
*/
/*-----*/
translate_wordstar_file_to_joined_html(
    char *wordstar_file,
    int html_out,
    char *internal_link_label,
    char *wordstar_file_title
)
{
    int bytes_read, f_in;
    int start_point_offset = 80000
    unsigned char input_buffer[10000000];
    f_in = open(wordstar_file, O_RDONLY|O_BINARY);
    if(f_in == -1) return(-1);
    /*create a label, containing the title */
    write_s(html_out, "\r\n<HR>\r\n<H2 id=\"");
    write_s(html_out, internal_link_label
    write_s(html_out, "\">\r\n
    write_html_s(html_out, wordstar_file_title);
    write_s(f_out, "</H2>\r\n<HR>\r\n");
    /* read the file into a buffer. Leave 80K vacant up front */
    bytes_read = read(
        f_in,
        (input_buffer+start_point_offset),
        (sizeof(input_buffer)-start_point_offset)
    );
    if(bytes_read <= 1) return(-3);
    parse_buffer(
        html_out,
        input_buffer,
        sizeof(input_buffer),
        start_point_offset,
        bytes_read
    );
    /* now close the wordstarinput file*/
    close(f_in);
    return(1);
}
/*Opens */
/*-----*/
make_table_of_contents_entry( int f_tc_out,
    char *file_linked_to,
    char *title
)
{
    new_fn_ext[32]
    file_name_and_ext_of_filespec(&new_fn_ext, file_linked_to);
    write_s(f_tc_out, "\r\n<P><A href=\"");
    write_s(f_tc_out, &new_fn_ext
    write_s(f_tc_out, "\">\r\n");
    write_html_s(f_tc_out, title);
    write_s(f_tc_out, "</A><P>");
}
/*-----*/
make_internal_table_of_contents_entry( int f_tc_out,
    char *internal_link_label,
    char *title
)
{
    write_s(f_tc_out, "\r\n<P><A href=\"");
    write_s(f_tc_out, internal_link_label);
    write_s(f_tc_out, "\">\r\n");
    write_html_s(f_tc_out, title);
    write_s(f_tc_out, "</A><P>");
}
/*-----*/
create_a_html_header(int f_out, char *title)
{
    write_s(f_out, "<HTML>\r\n<HEAD>\r\n<TITLE>");
    write_html_s(f_out, dir_name);
    write_s(f_out, "</TITLE>\r\n</HEAD>\r\n<BODY>\r\n");
}
/*-----*/

```

```

int open_output_html_wordstar_title_file(char *dir_spec)
{
    char titles_pf_file_spec[256], dir_title[256], pf_title[256];
    sprintf(
        &titles_pf_file_spec,
        "%s/%s_TITLES_PF.html",
        dir_spec,
        file_name_and_ext_of_filespec(dir_spec)
    );
    sprintf(
        &dir_titl,
        "%s %s",
        dir_spec,
        pf_title_of_directory(&pf_title, dir_spec)
    );
    f_out=open_output_html_file_w_title(
        &titles_pf_file_spec, &dir_title);
    return(f_out);
}
/*-----*/
int open_output_html_file_w_title(char *file_spec, char *title)
{
    int f_out,
    f_out = open(
        file_spec,
        O_WRONLY|O_CREAT|O_EXCL|O_BINARY, S_IREAD|S_IWRITE
    );
    if (f_out == -1) return(-1);
    else
    {
        create_a_html_header(f_out, title);
        return(f_out);
    }
}
/*-----*/
close_output_html_file(int f_out)
{
    write_s(f_out, "\r\n</BODY>\r\n</HTML>");
    close(f_out);
}
/*-----*/
/* Process a Particular WordStar Document */
/*-----*/
parse_buffer( int f_out,
              unsigned char input_buffer[],
              int size_of_buffer,
              int start_point_offset,
              int number_of_bytes
              )
{
    char curr_c, c_s, next_c, c_after_next;

    int index_to_buffer;

    manage_flip_flop_char_attr(f_out, curr_c, "initialize");
    set_curr_column("hard");
    set_ruler_mode(f_out, "reset");
    /* strip off Cntrl-Z's from the end */
    for(
        index_to_buffer=start_point_offset+number_of_bytes;
        index_to_buffer >= start_point_offset;
        index_to_buffer--
    )
    {
        if(input_buffer[index_to_buffer] != '\x1a')
        {
            number_of_bytes= index_to_buffer-start_point_offset;
            break
        }
    }
}
/*
Wordstar was originally a CP/M program,
and was mechanically translated to MS-DOS v.1,
using a "Cross-Assembler." Consequently,
Wordstar 3 used the old record-oriented file system,
in which files were allocated, read, and written,
in chunks of 128 bytes. Hence, Cntrl-Z was used
to pad the file out to the nearest whole record length.

Cross assemblers should doubtless be explained for the record.
The Intel 8086/8088-MS--DOS v,1 architecture was not a
superset of th Zilog Z-80--CP/M architecture,
but it was a superset of something which had a
one-to-one correspondence with the Zilog--CP/M
architecture. The assembly-language source code
for a CP/M program could be run through a cross-assembler
which would apply a series of
regular transformations, producing MS-DOS
assembly-language source code, which required
only a moderate amount of rewriting to be correct.
Thus the IBM PC began life with a large variety
of available commercial software.
*/
/*and now do the conversion */

```

```

for(
    index_to_buffer=start_point_offset;
    index_to_buffer <= start_point_offset+number_of_bytes ;
    index_to_buffer++
)
/*
Do over number_of_bytes from Start_point_offset,
but additional material may be patched in at the front,
and used up,
which is why there is an offset.
*/
{
    curr_c=input_buffer[index_to_buffer];
    c_s = curr_c & '\x7f';
    next_c=input_buffer[index_to_buffer+1];
    c_after_next=input_buffer[index_to_buffer+2];
}

```

```

/*case 1*/
/*disambiguate periods*/
if(curr_c == ".")
{
    if(set_curr_column("report") == -1) /* if it is a dot command*/
        index_to_buffer=
            parse_dot_command(
                f_out, input_buffer. index_to_buffer);
    else /*if it is only a period*/
    {
        send_char_to_html(f_out, curr_c);
        set_curr_column("incr");
    }
}
/*
WordStar "dot-commands" are user visible,
and are fully described in the user manual.
*/
/*case 2*/
else if((curr_c == ' ') || (curr_c == '\xa0')) /*SPACES*/
    index_to_buffer=
        parse_spaces(
            f_out, input_buffer. index_to_buffer);
/*case 3*/
else if( isprint(curr_c)) /*PRINTABLE*/
{
    send_char_to_html(f_out, curr_c);
    set_curr_column("incr");
}
/*case 3a*/
else if( isprint(c_s)) /* PRINTABLE WITH HIGH BIT */
{
    send_char_to_html(f_out, c_s);
    set_curr_column("incr");
}
/*case 4*/
else if( curr_c == '\r') /*Cntrl-M HARD CARRIAGE RETURN*/
{
    write_cr_according_to_ruler(f_out);
    if(next_c == '\n') index_to_buffer++;
    set_curr_column("hard");
    manage_flip_flop_char_attr(f_out, curr_c, "reset");
    /* makes the assumption that special
attributes dont persist across a
paragraph break */
}
/*case 5*/
else if( curr_c == '\x8d') /*SOFT CARRIAGE RETURN*/
{
    set_curr_column("soft");
    write_s(f_out, "\r\n");
    if(next_c == '\n') index_to_buffer++;
}
/*case 6*/
else if( curr_c == '\x0c') /*Cntrl-L-- Page Break*/
{
    write_cr_according_to_ruler(f_out);
    if(next_c == '\n') index_to_buffer++;
    set_curr_column("hard");
    manage_flip_flop_char_attr(f_out, curr_c, "reset");
    /* makes the assumption that special
attributes dont persist across a
page break */
}
}
/*case 7*/
/*
In Wordstar, a number of Cntrl-bytes toggle the print
attribute of text. IN HTML, the attributes have different tags
to turn them off and on. So we have to keep track of the
state of the Wordstar document,
and select the appropriate HTML tag.
*/
else if(
    (curr_c == '\x02' /* Cntrl-B Bold */)
    ||
    (curr_c == '\x04' /* Cntrl-D Double */)
    ||
    (curr_c == '\x0b' /* Cntrl-K Indexed */)
    ||
    (curr_c == '\x13' /* Cntrl-S Underline */)
    ||
    (curr_c == '\x14' /* Cntrl-T SuperScript */)
    ||
    (curr_c == '\x16' /* Cntrl-V Subscript */)
    ||
    (curr_c == '\x18' /* Cntrl-X Strikeout */)
    ||
    (curr_c == '\x19' /* Cntrl-Y Italics */)
) manage_flip_flop_char_attr(f_out, curr_c, "toggle");

/*
case 8
if it is an extended character,
that is: [hex 1b][ext_char][hex 1c]
*/
else if( curr_c == '\x1b') /* Cntrl-[ */
{
    if(c_after_next == '\x1c') /* Cntrl-\ */
    {
        set_curr_column("incr");
        send_ext_char_to_html(f_out, next_c);
        index_to_buffer+=2;
    }
    else write_hex_code(f_out, '\x1b');
}
/*
case 9
Cntrl-H Overprint
A common ad-hoc method of forming extended characters
*/
else if( curr_c == '\x08');
    write_s(
        f_out,
        "[Overprint]"
    );
/*
case 10
Cntrl-I Tab
PROBLEM
*/
else if( curr_c == '\x09')
{
    set_curr_column("incr");
    write_s(f_out, "[TAB]");
}
/*
case 11
Unpaired Line Feed
*/
else if( curr_c == '\x0a')
    write_s(f_out, "<P>[LINE FEED]<P>");
/*
case 12
Custom Print Controls--
only decodable by reference to printer manual
and dot-X commands, wordstar configration settings
*/
else if( curr_c == '\x05')
    write_s(
        f_out,
        "<P>/r/n[Cntrl-E -- Custom Print Control]/r/n<P>"
    );
else if( curr_c == '\x11')
    write_s(
        f_out,
        "<P>/r/n[Cntrl-Q -- Custom Print Control]/r/n<P>"
    );
else if( curr_c == '\x12')
    write_s(
        f_out,
        "<P>/r/n[Cntrl-R -- Custom Print Control]/r/n<P>"
    );
else if( curr_c == '\x17')
    write_s(
        f_out,
        "<P>/r/n[Cntrl-W -- Custom Print Control]/r/n<P>"
    );
}
/*case 13 Reserved Characters*/
else if( curr_c == '\x10')
    write_s(
        f_out,
        "<P>/r/n[Cntrl-P -- Reserved Char]/r/n<P>"
    );
else if( curr_c == '\x15')
    write_s(
        f_out,
        "<P>/r/n[Cntrl-U -- Reserved Char]/r/n<P>"
    );
}
/*
case 14
Cntrl-At-- Obsolete--fix Print Position
*/
else if( curr_c == '\x00')
    write_s(
        f_out,
        "[Cntrl-At -- fix Print Position ]/r/n<P>"
    );
}

```

```

/* case 15
old font change mechnism,
superseded by symetric sequence 15h,
and should have been automatically striped out
if edited under version 5 and subsequent
*/
else if( curr_c == '\x01')
write_s(
f_out,
"<P>/r/n[Ctrl-A -- Altrenative Font]/r/n<P>"
);
else if( curr_c == '\x0e')
write_s(
f_out,
"<P>/r/n[Ctrl-N -- Return to Normal Font]/r/n<P>"
);
/*
case 16
Ctrl-C -- Obsolete--
Pause For User Response During Print.
In other words, the user was expected to look at
what the printer had printed off,
insert a special daisywheel print element
or change a printer ribbon,
and resume.
*/
else if( curr_c == '\x03')
write_s(
f_out,
"<P>/r/n[Ctrl-C -- Meaning Unrecoverable]/r/n<P>"
);
/* case 17
Daisywheel Phantom characters
Meaningful only if you know which daisywheel was being used.
*/
else if( curr_c == '\x06' /* Ctrl-F */)
write_s(
f_out,
"[Daisywheel Phantom Space]>"
);
else if( curr_c == '\x07' /* Ctrl-G */)
write_s(
f_out,
"[Daisywheel Phantom Rubout]"
);
/*case 18*/
else if( curr_c == '\x0f' /* Ctrl-O -- Binding space*/)
;
/*
case 19
Ctrl-Z -- End of File used as padding at the end
of the file to bring it up to a round length
under C/PM and MS-DOS v.1. However, if it
occurs in the middle of the file, print the bytecode.
*/
else if( curr_c == '\x1a')
write_s(f_out, "[hex code 1a]");
/*
case 20
Symetric Sequences
*/
else if( curr_c == '\x1d' /* Ctrl-Right-Bracket -- */)
index_to_buffer=
parse_symetric_sequence(
f_out, input_buffer. index_to_buffer);
/*
case 21
Soft Hyphen
*/
else if( curr_c == '\x1e' /* Ctrl-Caret -- */)
;
else if( curr_c == '\x1f' /* Ctrl-Under_Hyphen -- */)
;
/*
case 22
Any Other Byte
put out the hex code and let the user figure out what it means
*/
else write_hex_code(f_out, curr_c);
}
}

```

```

/*-----*/
/*
In Wordstar, a number of Cntrl-bytes toggle the print
attribute of text. IN HTML, the attributes have different tags
to turn them off and on. So we have to keep track of the
state of the Wordstar document,
and select the appropriate HTML tag.
*/
manage_flip_flop_char_attr(int f_out, char curr_c, char *mode )
{
int static is_attr[8], save_attr[8];
int i;
/* define the names of the text state counters */
int bold_attr = 0;
int doub_attr = 1;
int undl_attr = 2;
int sup_attr = 3;
int sub_attr = 4;
int ital_attr = 5;
int strikeout_attr = 6;
int indexed_attr =7;
if (strcmp(mode, "toggle") == 0)
{
if( curr_c == '\x02' /*Ctrl-B*/)
flip_attr(&is_attr, bold_attr, f_out, "<B>", "</B>", "toggle");
else if( curr_c == '\x04' /*Ctrl-D*/)
flip_attr(&is_attr, doub_attr, f_out, "<B>", "</B>", "toggle");
else if( curr_c == '\x0b' /*Ctrl-B*/)
flip_attr(&is_attr, indexed_attr, f_out, "<?>", "</?>", "toggle");
else if( curr_c == '\x13' /*Ctrl-S*/)
flip_attr(&is_attr, undl_attr, f_out, "<U>", "</U>", "toggle");
else if( curr_c == '\x14' /*Ctrl-T*/)
flip_attr(&is_attr, sup_attr, f_out, "<SUP>", "</SUB>", "toggle");
else if( curr_c == '\x16' /*Ctrl-V*/)
flip_attr(&is_attr, sub_attr, f_out, "<SUB>", "</SUB>", "toggle");
else if( curr_c == '\x18' /*Ctrl-X*/)
flip_attr(&is_attr,
strikeout_attr, f_out, "<S>", "</S>", "toggle");
else if( curr_c == '\x19' /*Ctrl-Y*/)
flip_attr(&is_attr, ital_attr, f_out, "<EM>", "</EM>", "toggle");
}
else if (strcmp(mode, "restore") == 0)
{
if( is_attr[bold_attr] != save_attr[bold_attr] /*Ctrl-B*/)
flip_attr(&is_attr, bold_attr, f_out, "<B>", "</B>", "toggle");
if( is_attr[doub_attr] != save_attr[doub_attr] /*Ctrl-D*/)
flip_attr(&is_attr, doub_attr, f_out, "<B>", "</B>", "toggle");
if( is_attr[indexed_attr] != save_attr[indexed_attr] /*Ctrl-D*/)
flip_attr(&is_attr, indexed_attr, f_out, "<?>", "</?>", "toggle");
if( is_attr[undl_attr] != save_attr[undl_attr] /*Ctrl-S*/)
flip_attr(&is_attr, undl_attr, f_out, "<U>", "</U>", "toggle");
if( is_attr[sup_attr] != save_attr[sup_attr] /*Ctrl-T*/)
flip_attr(&is_attr, sup_attr, f_out, "<SUP>", "</SUB>", "toggle");
if( is_attr[sub_attr] != save_attr[sub_attr] /*Ctrl-V*/)
flip_attr(&is_attr, sub_attr, f_out, "<SUB>", "</SUB>", "toggle");
if( is_attr[strikeout_attr] != save_attr[strikeout_attr] /*Ctrl-X*/)
flip_attr(&is_attr,
strikeout_attr, f_out, "<S>", "</S>", "toggle");
if( is_attr[ital_attr] != save_attr[ital_attr] /*Ctrl-Y*/)
flip_attr(&is_attr, ital_attr, f_out, "<EM>", "</EM>", "toggle");
}
}

```

```

else if(strcmp(mode,"initialize" ) == 0)
{
    int i;
    for(i=0;i < 8; i++)
    {
        is_attr[i] = 0;
    }
}
else if(strcmp(mode,"save" ) == 0)
{
    int i;
    for(i=0;i < 8; i++)
    {
        save_attr[i] = is_attr[i];
    }
}
else if(strcmp(mode,"reset" ) == 0)
{
    flip_attr(&is_attr, bold_attr, f_out, "<B>", "</B>", "reset");
    flip_attr(&is_attr, doub_attr, f_out, "<B>", "</B>", "reset");
    flip_attr(&is_attr, indexed_attr, f_out, "<?>", "</?>", "reset");
    flip_attr(&is_attr, undl_attr, f_out, "<U>", "</U>", "reset");
    flip_attr(&is_attr, sup_attr, f_out, "<SUP>", "</SUB>", "reset");
    flip_attr(&is_attr, sub_attr, f_out, "<SUB>", "</SUB>", "reset");
    flip_attr(&is_attr, strikeout_attr, f_out, "<S>", "</S>", "reset");
    flip_attr(&is_attr, ital_attr, f_out, "<EM>", "</EM>", "reset");
}
}
/*-----*/
flip_attr(int *is_attr, int this_attr, int f_out, char *beg_str, char
*end_str, char *mode)
{
    if(is_attr[this_attr])
    {
        is_attr[this_attr] = 0;
        write_s(f_out, end_str);
    }
    else if(strcmp(mode, "reset") == 0)
    {
        is_attr[this_attr] = 1;
        write_s(f_out, beg_str);
    }
}
/* rewrite to localize this as far as possible. a;; the main program needs
to know is that the following characters are flip attributes, and that
something appropriate is being put in the output stream. there are three
possible cases, initialize, reset, and encounter a bytecode*/
/*-----*/
int set_curr_column(char *mode)
{
    static int curr_coll,save_coll;
    if(strcmp(mode,"hard" ) == 0) curr_coll = -1;
    else if(strcmp(mode,"soft" ) == 0) curr_coll = 0;
    else if(strcmp(mode,"incr" ) == 0)
    {
        if(curr_coll == -1) curr_coll = 1;
        else curr_coll++;
    }
    else if(strcmp(mode,"save" ) == 0) save_coll = curr_coll;
    else if(strcmp(mode,"restore" ) == 0) curr_coll = save_coll;
    else if(strcmp(mode,"report" ) == 0);
    return(curr_coll);
}
/*
    returns -1 after a hard carriage return,
    0 after a soft carriage return,
    otherwise the number of printable characters
    now read into the line
*/
/*-----*/
write_hex_code(int f_out, char c)
{
    char c1, c2, c1c, c2c;
    char[16] char_rep= "[hex code bb]";
    c2=c%16; /*modulo off the high order nybble*/
    c1=(c-c2)/16; /* and subtract to obtain the remainder*/
    if(c1 <= 9) c1c = c1 + '0';
        else c1c = c1 + 'A'-10;
    if(c2 <= 9) c2c = c2 + '0';
        else c2c = c2 + 'A'-10;
    char_rep[11] = c1c;
    char_rep[12] =c2c;
    write_s(f_out, &char_rep);
}
/*-----*/
send_char_to_html(int f_out, char c)
{
    char send_str[2];
    if(c == "\\") write_s(f_out, "&quot;");
    else if(c == "&") write_s(f_out, "&amp;");
    else if(c == "<") write_s(f_out, "&lt;");
    else if(c == ">") write_s(f_out, "&gt;");
    else
    {
        send_str[0] = c;
        send_str[1] = '\0';
        write_s(f_out, &send_str);
    }
}
/*provides aliasing for source characters which are reserved in HTML*/
/*-----*/
write_html_s(int f_out, char *s)
{
    char *s1;
    for(s1=s; *s1 != '\0'; s1++) send_char_to_html(f_out, *s1);
}
/*-----*/
write_s(int f_out, char *s)
{
    write(f_out, s, strlen(s));
}
/* the general output point*/

```

```

/*-----*/
send_ext_char_to_html(int f_out, char c)
{
    switch(c)
    {
        case '\x00': write_s(f_out, " "); break; /*blank*/
        case '\x01': write_s(f_out, "[happy_face]"); break; /*happy face*/
        case '\x02': write_s(f_out, "[inv_happy_face]"); break;
        case '\x03': write_s(f_out, "&heartsuit;"); break; /*heart*/
        case '\x04': write_s(f_out, "&diamondsuit;"); break; /*diamond*/
        case '\x05': write_s(f_out, "&clubsuit;"); break; /*club*/
        case '\x06': write_s(f_out, "&spadesuit;"); break; /*spade*/
        case '\x07': write_s(f_out, "&bullet;"); break; /*bullet*/
        case '\x08': write_s(f_out, "[inv_bullet]"); break; /*inverse bullet*/
        case '\x09': write_s(f_out, "&xcirc;"); break; /*circle*/
        case '\x0a': write_s(f_out, "[inv_circle]"); break; /*inverse circle*/
        case '\x0b': write_s(f_out, "&male;"); break; /*male sign*/
        case '\x0c': write_s(f_out, "&female;"); break; /*female sign*/
        case '\x0d': write_s(f_out, "&sung;"); break; /*single note*/
        case '\x0e': write_s(f_out, "&sung;&sung;"); break; /*double note*/
        case '\x0f': write_s(f_out, "[sun]"); break; /*sun*/

        case '\x10': write_s(f_out, "&rtfrf;"); break; /*right triangle*/
        case '\x11': write_s(f_out, "&ltrfrf;"); break; /*left triangle*/
        case '\x12': write_s(f_out, "&updownarrow;"); break; /*up-down arrow*/
        case '\x13': write_s(f_out, "!!"); break; /*double exclamation*/
        case '\x14': write_s(f_out, "&para;"); break; /*paragraph sign*/
        case '\x15': write_s(f_out, "&sect;"); break; /*section sign*/
        case '\x16': write_s(f_out, "&hybull;"); break; /*rectangular bullet*/
        case '\x17': write_s(f_out, "&UpArrowBar;&DownArrowBar;"); break;
        case '\x18': write_s(f_out, "&uparrow;"); break; /*up arrow*/
        case '\x19': write_s(f_out, "&downarrow;"); break; /*down arrow*/
        case '\x1a': write_s(f_out, "&rightrightarrow;"); break; /*right arrow*/
        case '\x1b': write_s(f_out, "&leftarrow;"); break; /*left arrow*/
        case '\x1c': write_s(f_out, "&boxur;"); break; /*lower left box*/
        case '\x1d': write_s(f_out, "&leftrightarrow;"); break;
        case '\x1e': write_s(f_out, "&blacktriangle;"); break; /*up triangle*/
        case '\x1f': write_s(f_out, "&blacktriangledown;"); break;
        case '\x20': write_s(f_out, "&Ccedil;"); break;
        case '\x21': write_s(f_out, "&uuml;"); break;
        case '\x22': write_s(f_out, "&acute;"); break;
        case '\x23': write_s(f_out, "&acirc;"); break;
        case '\x24': write_s(f_out, "&auml;"); break;
        case '\x25': write_s(f_out, "&agrave;"); break;
        case '\x26': write_s(f_out, "&aring;"); break;
        case '\x27': write_s(f_out, "&ccedil;"); break;

        case '\x28': write_s(f_out, "&ecirc;"); break;
        case '\x29': write_s(f_out, "&euml;"); break;
        case '\x2a': write_s(f_out, "&egrave;"); break;
        case '\x2b': write_s(f_out, "&iuml;"); break;
        case '\x2c': write_s(f_out, "&icirc;"); break;
        case '\x2d': write_s(f_out, "&igrave;"); break;
        case '\x2e': write_s(f_out, "&Auml;"); break;
        case '\x2f': write_s(f_out, "&Aring;"); break;

        case '\x30': write_s(f_out, "&Eacute;"); break;
        case '\x31': write_s(f_out, "&aelig;"); break;
        case '\x32': write_s(f_out, "&Aelig;"); break;

        case '\x33': write_s(f_out, "&ocirc;"); break;
        case '\x34': write_s(f_out, "&ouml;"); break;
        case '\x35': write_s(f_out, "&ograve;"); break;
        case '\x36': write_s(f_out, "&ucirc;"); break;
        case '\x37': write_s(f_out, "&ugrave;"); break;
        case '\x38': write_s(f_out, "&yuml;"); break;
        case '\x39': write_s(f_out, "&ouml;"); break;
        case '\x3a': write_s(f_out, "&Uuml;"); break;

        case '\x3b': write_s(f_out, "&cent;"); break;
        case '\x3c': write_s(f_out, "&pound;"); break;
        case '\x3d': write_s(f_out, "&yen;"); break;
        case '\x3e': write_s(f_out, "[Pt]"); break; /*Pt sign*/

        case '\x3f': write_s(f_out, "[funct]"); break; /*the function mark*/

        case '\xa0': write_s(f_out, "&aacute;"); break;
        case '\xa1': write_s(f_out, "&iacute;"); break;
        case '\xa2': write_s(f_out, "&oacute;"); break;
        case '\xa3': write_s(f_out, "&uacute;"); break;
        case '\xa4': write_s(f_out, "&ntilde;"); break;
        case '\xa5': write_s(f_out, "&ntilde;"); break;
        case '\xa6': write_s(f_out, "&amacr;"); break;
        case '\xa7': write_s(f_out, "&omacr;"); break;

        case '\xa8': write_s(f_out, "&iquest;"); break;
        case '\xa9': write_s(f_out, "&boxdr;"); break; /*upper left box*/
        case '\xaa': write_s(f_out, "&boxdl;"); break; /*upper right box*/
        case '\xab': write_s(f_out, "&frac12;"); break;
        case '\xac': write_s(f_out, "&frac14;"); break;
        case '\xad': write_s(f_out, "!!"); break; /*opening (spanish) exclamation

        point*/
        case '\xae': write_s(f_out, "&laquo;"); break; /*<< mark*/
        case '\xaf': write_s(f_out, "&raquo;"); break; /*>> mark*/
        case '\xb0': write_s(f_out, "&blk14;"); break; /*light block*/
        case '\xb1': write_s(f_out, "&blk12;"); break; /*medium block*/
        case '\xb2': write_s(f_out, "&blk34;"); break; /*dark block*/

        case '\xb3': write_s(f_out, "&boxv;"); break; /*single vertical*/
        case '\xb4': write_s(f_out, "&boxvl;"); break; /*single right junction*/
        case '\xb5': write_s(f_out, "&boxvl;"); break; /*2 to 1 right junction*/
        case '\xb6': write_s(f_out, "&boxvl;"); break; /*1 to 2 right junction*/
        case '\xb7': write_s(f_out, "&boxDL;"); break; /*1 to 2 upper right*/
        case '\xb8': write_s(f_out, "&boxDL;"); break; /*2 to 1 upper right*/
        case '\xb9': write_s(f_out, "&boxVL;"); break; /*double right junction*/
        case '\xba': write_s(f_out, "&boxV;"); break; /*double vertical*/
        case '\xbb': write_s(f_out, "&boxDL;"); break; /*double upper right*/
        case '\xbc': write_s(f_out, "&boxUL;"); break; /*double lower right*/
        case '\xbd': write_s(f_out, "&boxUL;"); break; /*1 to 2 lower right*/
        case '\xbe': write_s(f_out, "&boxUL;"); break; /*2 to 1 lower right*/
        case '\xbf': write_s(f_out, "&boxdl;"); break; /*single upper right*/
        case '\xc0': write_s(f_out, "&boxur;"); break; /*single lower left*/
        case '\xc1': write_s(f_out, "&boxhu;"); break; /*single lower junction*/
        case '\xc2': write_s(f_out, "&boxhd;"); break; /*single upper junction*/
        case '\xc3': write_s(f_out, "&boxvr;"); break; /*single left junction*/
        case '\xc4': write_s(f_out, "&boxh;"); break; /*single horizontal*/
        case '\xc5': write_s(f_out, "&boxvh;"); break; /*single intersection*/
        case '\xc6': write_s(f_out, "&boxvR;"); break; /*2 to 1 left junction*/
        case '\xc7': write_s(f_out, "&boxvR;"); break; /*1 to 2 left junction*/
        case '\xc8': write_s(f_out, "&boxUR;"); break; /*double lower left*/
        case '\xc9': write_s(f_out, "&boxDR;"); break; /*double upper left*/
        case '\xca': write_s(f_out, "&boxHU;"); break; /*double lower junction*/
        case '\xcb': write_s(f_out, "&boxHD;"); break; /*double upper junction*/
        case '\xcc': write_s(f_out, "&boxVR;"); break; /*double left junction*/
        case '\xcd': write_s(f_out, "&boxH;"); break; /*double horizontal*/
        case '\xce': write_s(f_out, "&boxvH;"); break; /*double intersection*/
        case '\xcf': write_s(f_out, "&boxHu;"); break; /*1 to 2 lower junction*/
        case '\xd0': write_s(f_out, "&boxHd;"); break; /*2 to 1 lower junction*/
        case '\xd1': write_s(f_out, "&boxHd;"); break; /*1 to 2 upper junction*/
        case '\xd2': write_s(f_out, "&boxHD;"); break; /*2 to 1 upper junction*/
        case '\xd3': write_s(f_out, "&boxUr;"); break; /*1 to 2 lower left*/
        case '\xd4': write_s(f_out, "&boxUr;"); break; /*2 to 1 lower left*/
        case '\xd5': write_s(f_out, "&boxDR;"); break; /*1 to 2 upper left*/
        case '\xd6': write_s(f_out, "&boxHU;"); break; /*2 to 1 intersection*/
        case '\xd7': write_s(f_out, "&boxvH;"); break; /*1 to 2 intersection*/
        case '\xd8': write_s(f_out, "&boxul;"); break; /*single lower right*/
        case '\xd9': write_s(f_out, "&boxul;"); break; /*single lower right*/
        case '\xda': write_s(f_out, "&boxdr;"); break; /*single upper left*/

        case '\xdb': write_s(f_out, "&block;"); break; /*inverse space*/
        case '\xdc': write_s(f_out, "&lhlbk;"); break; /*lower inverse*/
        case '\xdd': write_s(f_out, "&marker;"); break; /*left inverse*/
        case '\xde': write_s(f_out, "&marker;"); break; /*right inverse*/
        case '\xdf': write_s(f_out, "&uhblk;"); break; /*upper inverse*/

        case '\xe0': write_s(f_out, "&alpha;"); break;
        case '\xe1': write_s(f_out, "&beta;"); break;
        case '\xe2': write_s(f_out, "&gamma;"); break;
        case '\xe3': write_s(f_out, "&pi;"); break;
        case '\xe4': write_s(f_out, "&sigma;"); break;
        case '\xe5': write_s(f_out, "&sigma;"); break;
        case '\xe6': write_s(f_out, "&mu;"); break;
        case '\xe7': write_s(f_out, "&tau;"); break;
        case '\xe8': write_s(f_out, "&phi;"); break;
        case '\xe9': write_s(f_out, "&theta;"); break;
        case '\xea': write_s(f_out, "&omega;"); break;
        case '\xeb': write_s(f_out, "&delta;"); break;
        case '\xec': write_s(f_out, "[infinity]"); break; /*infinity*/
        case '\xed': write_s(f_out, "&straightphi;"); break;
        case '\xee': write_s(f_out, "&epsilon;"); break;

        case '\xef': write_s(f_out, "&Intersection;"); break;
        case '\xf0': write_s(f_out, "&Congruent;"); break; /*is identical to*/
        case '\xf1': write_s(f_out, "&PlusMinus;"); break;
        case '\xf2': write_s(f_out, "&ge;"); break; /*greater than or equal*/
        case '\xf3': write_s(f_out, "&le;"); break; /*less than or equal to*/
        case '\xf4': write_s(f_out, "&Integral;"); break; /*top half integral*/
        case '\xf5': write_s(f_out, "&Integral;"); break; /*lower half integral*/
        case '\xf6': write_s(f_out, "&divide;"); break; /*divide by*/
        case '\xf7': write_s(f_out, "&approx;"); break; /*approximately*/
        case '\xf8': write_s(f_out, "&deg;"); break; /*degree sign*/
        case '\xf9': write_s(f_out, "[filled_deg]"); break;
        case '\xfa': write_s(f_out, "&sqf;"); break; /*small bullet*/
        case '\xfb': write_s(f_out, "[sqrt]"); break; /*square root*/
        case '\xfc': write_s(f_out, "[sup n]"); break; /*superscript n*/
        case '\xfd': write_s(f_out, "&sup2;"); break; /*superscript 2*/
        case '\xfe': write_s(f_out, "[small box]"); break; /*small box*/
        case '\xff': write_s(f_out, " "); break; /*phantom space*/
    }
}

```



```

/*
Font
*/
case '\x02' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
Tabs and Dot Leaders
*/
case '\x09' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
End of Page-- Wordstar reccomends ignoring this
*/
case '\x0b' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
Page Offset-- Wordstar says this should not occur in files,
only in printer drivers
*/
case '\x0c' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
Paragraph Number
*/
case '\x0d' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
Index Item
*/
case '\x0e' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
User Print Control
*/
case '\x0f' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
Paragraph Style
*/
case '\x11' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
Alternate/Normal Font Change
*/
case '\x15' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
Truncation
*/
case '\x16' :
{
return(index_to_last_byte_in_sequence);
break;
}
/*
*/
default:
{
return(index_to_last_byte_in_sequence);
break;
}
} /* end switch */
}
/*
returns index of last byte which is still in the buffer,
and has been processed, so normal incrementing of the index

```

```

by the for-loopwill get one to a new byte,
*/
-----*/
int select_note_action(
unsigned char opcode,
int f_out,
unsigned char input_buffer[],
int index_to_first_byte_in_sequence
int index_to_last_byte_in_sequence
)
{
int bytes_added_to_stream;
unsigned char c_1;
switch(opcode)
{
/*
*/
case '\x03':
case '\x04':
case '\x05':
case '\x06':
{
/* save and reset toggles and flags */
manage_flip_flop_char_attr(f_out, c_1, "save");
manage_flip_flop_char_attr(f_out, c_1, "reset");
set_curr_column("save");
set_curr_column("hard");
set_ruler_mode(f_out, "save");
bytes_added_to_stream=
parse_note(
f_out,
input_buffer,
index_to_first_byte_in_sequence
index_to_last_byte_in_sequence
);
return(bytes_added_to_stream);
break;
}
/*
HTML </aside>
encoded in Wordstar format by function parse_note
The sequence will be of the form:
<1d><04><00><ff><04><00><1d>
*/
case '\xff' :
{
/*restore toggles and flags */
manage_flip_flop_char_attr(f_out, c_1, "restore");
set_curr_column("restore");
set_ruler_mode(f_out, "restore1");
/*output */
write_s(f_out, "</ASIDE>")
set_ruler_mode(f_out, "restore2");
return(0);
break;
}
}
}
}

```

```

/*-----*/
int parse_note(
    int f_out,
    unsigned char input_buffer[],
    int index_to_first_byte_in_sequence,
    int index_to_last_byte_in_sequence
);
{
    unsigned char opcode,
        conversion_flag, inner_conversion_flag;
    int internal_sequence_offset,
        line_count, internal_sequence_line_count,
        note_number, length_of_internal_sequence,
        fst_loc_inside_seq_index,
        last_loc_inside_seq_index,
        inside_length_of_sequence;
    char temp_digit_str[20];
    /*Break out the header fields*/
    opcode = input_buffer[index_to_first_byte_in_sequence+3];
    line_count=get_int16_from_byte_array(
        input_buffer,
        index_to_first_byte_in_sequence+4
    );
    internal_sequence_offset=get_int16_from_byte_array(
        input_buffer,
        index_to_first_byte_in_sequence+6
    );
    conversion_flag = input_buffer[index_to_first_byte_in_sequence+8];
    /* ... and the boundaries of the data section */
    fst_loc_inside_seq_index =
        index_to_first_byte_in_sequence+9;
    last_loc_inside_seq_index =
        index_to_last_byte_in_sequence-3;
    inside_length_of_sequence = last_loc_inside_seq_index
        -fst_loc_inside_seq_index
        +1;
    /*locate the internal sequence lf it exists */
    if(
        start_of_internal_sequence_index=is_there_an_internal_sequence(
            input_buffer,
            fst_loc_inside_seq_index,
            last_loc_inside_seq_index,
            &length_of_internal_sequence
        )
        != -1
    )
    {
        /*and break out its fields*/
        internal_sequence_line_count=
            get_int16_from_byte_array(
                input_buffer,
                start_of_internal_sequence_index+4
            );
        note_number=
            get_int16_from_byte_array(
                input_buffer,
                start_of_internal_sequence_index+6
            );
        inner_conversion_flag =
            input_buffer[start_of_internal_sequence_index+8];
        if(length_of_internal_sequence > 11)
        {
            for(i=0; i < length_of_internal_sequence-11 ; i++)
                internal_sequence_data[i]
                    =input_buffer[
                        start_of_internal_sequence_index
                        +8+i];
            internal_sequence_data[length_of_internal_sequence-11]=0;
        }
        else internal_sequence_data[0]=0;
        /*
         * and remove the internal sequence
         */
        inside_length_of_sequence
            = mem_xcise(
                &input_buffer[fst_loc_inside_seq_index],
                inside_length_of_sequence,
                &input_buffer[start_of_internal_sequence_index],
                length_of_internal_sequence
            );
    }
    /* ...and move the sequence to just before the terminal tag*/
    memmove(
        &input_buffer[
            index_to_last_byte_in_sequence
            -inside_length_of_sequence
            - 6
        ],
        &input_buffer[fst_loc_inside_seq_index],
        inside_length_of_sequence
    );
    /* ...and add the terminal tag, <1d><04><00><ff><04><00><1d>*/
    input_buffer[index_to_last_byte_in_sequence-6]=
        input_buffer[index_to_last_byte_in_sequence]='\x1d';

```

```

    input_buffer[index_to_last_byte_in_sequence-4]=
        input_buffer[index_to_last_byte_in_sequence-1]='\x00';
    input_buffer[index_to_last_byte_in_sequence-5]=
        input_buffer[index_to_last_byte_in_sequence-2]='\x04';
    input_buffer[index_to_last_byte_in_sequence-2]='\xff';
    /*Build a front tag, and sent it to the output*/
    write_s(f_out, "<ASIDE>")
    switch(opcode)
    {
        case 3: write_s(f_out, "Footnote"); break;
        case 4: write_s(f_out, "Endnote"); break;
        case 5: write_s(f_out, "Annotation"); break;
        case 6: write_s(f_out, "Comment"); break;
    }
    if(start_of_internal_sequence_index == -1)
        if(internal_sequence_offset > 0)
        {
            sprintf(&temp_digit_str, "%d",
                internal_sequence_offset);
            write_s(f_out, &temp_digit_str);
        }
    else if(
        (opcode == 3)
        ||
        (opcode != 4)
    )
    {
        sprintf(&temp_digit_str, "%d",note_number);
        write_s(f_out, &temp_digit_str);
    }
    write_s(f_out, ":",<P>")
    /* ...and return*/
    return(inside_length_of_sequence+7);
}
/*
 * returns the number of bytes inserted
 * each note will be converted to an "aside," "<aside>," and "</aside>"
 */
/*-----*/
int mem_xcise(void *dst_addr, size_t dst_len,void *src_addr, size_t
src_len)
{
    memmove(
        src_addr,
        src_addr+src_len,
        dst_len -(src_addr-dst_addr)-src_len
    );
    return(dst_len-src_len);
}
/*
 * excises source region [address and length]
 * from destination region [address and length],
 * and returns the new length of destination region
 */
/*-----*/
int is_there_an_internal_sequence(
    unsigned char input_buffer[],
    int fst_loc_inside_seq_index,
    int last_loc_inside_seq_index,
    int *length
)
{
    int i,j, last_possible_index_for_inner_sequence;
    last_possible_index_for_inner_sequence =
        last_loc_inside_seq_index-6;
    for(
        i=fst_loc_inside_seq_index;
        i >= last_possible_index_for_inner_sequence;
        i++
    )
    {
        if(
            (input_buffer[i] == '\x1d')
            &&
            (input_buffer[i-1] != '\x1b')
        )
        {
            if(
                (j= symmetric_sequence_is_valid(input_buffer, i)
                ==
                -1
            )
            )return(-1)
            else
            {
                *length=j-i;
                return(i);
            }
        }
    }
    return(-1)
}
/*
 */

```

```

Returns index of initiating [Hex 1D]
if there is a valid internal sequence, and sets length,
else returns -1

The Wordstar manual did not seem quite sure of itself,
where the location of internal sequences was concerned,
possibly commingling differences between versions 5,6,
and 7. I therefore opt for a brute-force approach,
which is comparatively foolproof
*/
/*-----*/
int symmetric_sequence_is_valid(
    unsigned char input_buffer[],
    int index_to_first_byte_in_sequence
)
{
    int offset, index_to_last_byte_in_sequence;
    offset=get_int16_from_byte_array(
        input_buffer,
        index_to_first_byte_in_sequence+1
    );

    index_to_last_byte_in_sequence=
        index_to_first_byte_in_sequence+offset+2;
    if(
        (input_buffer[index_to_first_byte_in_sequence] == '\x1d' )
        &&
        (input_buffer[index_to_last_byte_in_sequence] == '\x1d' )
        &&
        (
            get_int16_from_byte_array(
                input_buffer,
                index_to_last_byte_in_sequence-2
            )
            ==
            offset
        )
        &&
        (
            offset > 0
        )
    )return(index_to_last_byte_in_sequence);
    else return(-1);
}
/*returns index of terminating byte [Hex 1D] if valid, else -1*/
/*-----*/
int get_int16_from_byte_array(
    unsigned char byte_array[],
    int index_to_array
)
{
    unsigned char high_byte_of_integer, low_byte_of_integer;
    int_integer_16;
    high_byte_of_integer=
        input_buffer[index_to_first_byte_in_sequence+1];
    low_byte_of_integer=
        input_buffer[index_to_first_byte_in_sequence];
    integer_16 =
        (int)low_byte_of_offset + (256 * (int) high_byte_of_offset );
    return(integer_16);
}
/*
Obtains a 16-bit integer,
stored in a byte array in orthodox PC (little-endian),
fashion, given the index of the first byte
*/
/*-----*/
convert_image_to_html(
    int f_out,
    unsigned char input_buffer[],
    int index_to_first_byte_in_sequence,
    index_to_last_byte_in_sequence
)
{
    /* make the file name into a C string */
    input_buffer[index_to_last_byte_in_sequence-2]='\x00'
    write_s(f_out, "<img src=\"");
    write_s(f_out,
        &input_buffer[index_to_first_byte_in_sequence+3]
    );
    write_s(f_out, "\">")
}

```

```

/*-----*/
/* Handles Commands Encoded As Dot Commands */
/*-----*/
int parse_dot_command(
    int f_out,
    unsigned char input_buffer[],
    int index_to_buffer
)
{
    int index_of_last_byte_of_dot_command, index_of_cr;
    char *addr_of_cr;
    /*find next carriage return*/
    if(
        addr_of_cr
        =memchr(&input_buffer[index_to_buffer], '\r', 256)
        == NULL
    )
    {
        index_of_last_byte_of_dot_command=index_to_buffer;
        send_char_to_html(f_out, input_buffer[index_to_buffer]);
        set_curr_column("incr");
    }
    /*
    if there is not a hard carriage return
    in a reasonable distance, best assume
    it is a period after all
    */
    else
    {
        index_of_cr=addr_of_cr-input_buffer;
        /*and the following linefeed*/
        if(input_buffer[index_of_cr+1] == '\n')
            index_of_last_byte_of_dot_command = index_of_cr+1;
        else
            index_of_last_byte_of_dot_command = index_of_cr;
        /*
        which gives you the bounds of the dot command line,
        and the index to return.
        */
        set_curr_column("hard");
        manage_flip_flop_char_attr(f_out, curr_c, "reset");
        /*
        makes the assumption that special
        attributes dont persist across
        a dot command
        */
        input_buffer[index_of_cr] == '\0';
        process_dot_command(f_out, &input_buffer[index_to_buffer+1]);
    }
    /* Call it with the dot command, less dot, turned into a C string */
    return(index_of_last_byte_of_dot_command);
}
/*
returns index of last byte of the terminaing CR-LF,
so normal incrementing of the index
by the for-loopwill get one to a new byte,
*/
/*-----*/
process_dot_command(int f_out, char *command_string)
{
    if(strnicmp(command_string, "rr", 2) == 0)
        process_dot_ruler_command(f_out, command_string);
    else if(strnicmp(command_string, "fi", 2) == 0)
        process_dot_file_insert(f_out, command_string);
    else if(
        (strnicmp(command_string, "aw", 2) == 0)
        ||
        (strnicmp(command_string, "uj", 2) == 0)
        ||
        (strnicmp(command_string, "ps", 2) == 0)
        ||
        (strnicmp(command_string, "oc", 2) == 0)
        ||
        (strnicmp(command_string, "oj", 2) == 0)
        ||
        (strnicmp(command_string, "pf", 2) == 0)
    )
        process_dot__switch_reformat(f_out, command_string);
    else
    {
        write_s(f_out, "WORDSTAR DOT COMMAND: ");
        write_html_s(f_out, command_string);
        write_s(f_out, "\r\n<P>");
    }
}
/*
This is the Place for the enumeration of the dot commands.
Command string omits the leading period.
*/

```

```

/*-----*/
process_dot_file_insert(int f_out, char *command_string);
{
    write_s(f_out, "<A href=\"");
    write_s(f_out, command_string+3);
    write_s(f_out, "\">");
    write_html_s(f_out, command_string);
    write_s(f_out, "</A>\r\n<P>");
}
/*
We Translate "Insert File" as "Link to File."
*/
/*-----*/
process_dot_switch_reformat(int f_out, char *command_string)
{
    process_dot_command_on_off(f_out, command_string. "</pre>", "<pre>");
}
/*-----*/
process_dot_command_on_off(int f_out, char *command_string, char *on_code,
char *off_code)
{
    if(
        (strnicmp(command_string+3, "on", 2) == 0)
        ||
        (command_string[2] == '1') write_s(f_out, on_code);
    )
    elseif(
        (strnicmp(command_string+3, "off", 3) == 0)
        ||
        (command_string[2] == '0') write_s(f_out, off_code);
    )
}
/*-----*/
process_dot_ruler_command(int f_out, char *command_string)
{
    char ruler_type[30];
    int is_embedded_ruler_line;
    if(isdigit(command_string[2]))
    {
        ruler_type[0] = command_string[2];
        is_embedded_ruler_line = 0;
    }
    else if(
        (command_string[2] == ' ')
        &&
        isdigit(command_string[3])
    )
    {
        ruler_type[0] = command_string[3];
        is_embedded_ruler_line = 0;
    }
    /* a numbered ruler, with or without a space */
    else
    {
        ruler_type[0] = 'L';
        is_embedded_ruler_line = 1;
    }
    ruler_type[1] = '\0'; /* make it a string*/
    set_ruler_mode(f_out, ruler_type);
    if(is_embedded_ruler_line)
    {
        write_html_s(f_out, command_string);
        write_s(f_out, "\r\n<P>");
    }
}
/*
Determine the ruler type,
and, if embedded, output the format string.
*/

```

```

/*-----*/
set_ruler_mode(int f_out, char *ruler_type)
{
    static char current_mode, saved_mode;
    if(strcmp(ruler_type, "CR") == 0)
    {
        if(current_mode == '2')
            write_s(f_out, "\r\n</LI>\r\n<LI>");
        else write_s(f_out, "\r\n<P>");
    }
    else if(strcmp(ruler_type, "Reset") == 0)
        current_mode='0';
    else if(strcmp(ruler_type, "Save") == 0) /* Going Into a Note, Before the
<Aside> */
    {
        if(current_mode == '0'); /* No Change Required*/
        else if(current_mode == '1')
            write_s(f_out, "\r\n</BLOCKQUOTE>");
        else if(current_mode == '2')
            write_s(f_out, "\r\n</LI></UL>");
        else if(current_mode == 'L'); /* No Text Output Required */
            saved_mode=current_mode;
            current_mode='0';
    }
    else if(strcmp(ruler_type, "Restore1") == 0) /* Coming Back From a Note,
Before the </Aside> */
    {
        if(current_mode == '0')/* No Change Required at this Stage */
        else if(current_mode == '1')
            write_s(f_out, "\r\n</BLOCKQUOTE>");
        else if(current_mode == '2')
            write_s(f_out, "\r\n</LI></UL>");
        else if(current_mode == 'L')
            write_s(
                f_out,
                "\r\n<P>[End of Embedded Ruler Line]"
            );
        /* Brings the Text Back to Mode 0, as it was at the Start of the Note
*/
    }
    else if(strcmp(ruler_type, "Restore2") == 0) /* Coming Back From a Note,
after the </Aside> */
    {
        if(saved_mode == '0'); /* No Change Required*/
        else if(saved_mode == '1')
            write_s(f_out, "\r\n</BLOCKQUOTE>");
        else if(saved_mode == '2')
            write_s(f_out, "\r\n<UL><LI>");
        else if(current_mode == 'L'); /* No Text Output Required */
            current_mode=saved_mode;
    }
    else if(
        (strcmp(ruler_type, "0") == 0)
        || (strcmp(ruler_type, "3") == 0)
        || (strcmp(ruler_type, "4") == 0)
        || (strcmp(ruler_type, "5") == 0)
        || (strcmp(ruler_type, "6") == 0)
        || (strcmp(ruler_type, "7") == 0)
        || (strcmp(ruler_type, "8") == 0)
        || (strcmp(ruler_type, "9") == 0)
    ) /*Normal Mode*/
    {
        if(current_mode == '1')
            write_s(f_out, "\r\n</BLOCKQUOTE>");
        else if(current_mode == '2')
            write_s(f_out, "\r\n</LI></UL>");
        else if(current_mode == 'L')
            write_s(
                f_out,
                "\r\n<P>[End of Embedded Ruler Line]"
            );
        current_mode='0';
        if(strcmp(ruler_type, "0") != 0)
        { write_s(f_out, "\r\n<P> [Predefined Ruler type: ");
          write_s(f_out, ruler_type);
          write_s(f_out, "-- Format Unrecoverable\r\n<P>");
        }
    }
    else if(strcmp(ruler_type, "1") == 0) /*Block Quote */
    {
        if(current_mode == '0')
            write_s(f_out, "\r\n</BLOCKQUOTE>");
        else if(current_mode == '2')
            write_s(f_out, "\r\n</LI></UL></BLOCKQUOTE>");
        else if(current_mode == 'L')
            write_s(
                f_out,
                "\r\n<P>[End of Embedded Ruler Line]\r\n</BLOCKQUOTE>"
            );
        current_mode='1';
    }
}

```

```

else if(strcmp(ruler_type,"2") == 0) /* Outline */
{
    if(current_mode == '0')
        write_s(f_out, "\r\n<UL><LI>");
    else if(current_mode == '1')
        write_s(f_out, "\r\n</BLOCKQUOTE><UL><LI>");
    else if(current_mode == 'L')
        write_s(
            f_out,
            "\r\n<P>[End of Embedded Ruler Line]\r\n<UL><LI>"
        );
    current_mode='2';
}
else if(strcmp(ruler_type,"L") == 0)
{
    if(current_mode == '0')
        write_s(
            f_out,
            "\r\n<P>[Start Embedded Ruler Line]<P>\r\n"
        );
    else if(current_mode == '1')
        write_s(
            f_out,
            "\r\n</BLOCKQUOTE><P>[Start Embedded Ruler Line]<P>\r\n"
        );
    else if(current_mode == '2')
        write_s(
            f_out,
            "\r\n</LI></UL><P>[Start Embedded Ruler Line]<P>\r\n"
        );
    current_mode='L';
}
}
/*
Command Codes:0-9, L, Reset, CR, Save, Restore,
expressed as strings
Internal States: 0-9, L, expressed as a character

Predefined ruler lines can be set within the wordstar program,
which means they cannot be recovered from a wordstar file.
However. even if the user may have tinkered with the settings,
he will probably not have changed the
underlying intentions.
That said:
Predefined Ruler line 0: Normal.
1: Block Quote.
2: Outline,
which I gloss as Unordered List.
3-9: Purely User-Defined
*/
/*-----*/
write_cr_according_to_ruler(int f_out)
{
    set_ruler_mode(f_out,"CR")
}
/*
A special case of the Set Ruler Mode function,
labeled according to use.
*/
/*-----*/
/* To Handle Groups of Spaces which may have been "Justified." */
/*-----*/

parse_spaces(
    int f_out,
    unsigned char input_buffer[],
    int index_to_buffer
)
{
    int i, j;
    for(
        i=0;
        (input_buffer[index_to_buffer+i] == ' ')
        ||
        (input_buffer[index_to_buffer+i] == '\xa0')
        ;i++
    );
    for(j=0;j<i;j++) send_char_to_html(f_out, ' ');
}
/*
returns index of last byte of the group of spaces,
so normal incrementing of the index
by the for-loopwill get one to a new byte,
*/

```

```

/*-----*/
WordStar's page-formatting abilities were ample for the manuscript
of a nonscholarly book; suffiicient for that of an academic graduate
thesis
or dissertation, or an unpublished draft of a scholarly book;
marginal for the final preparation of a published bood,
depending on subject, publisher, and distribution method;
and totally inadequate for the produciton of a "glossy Magazine."

Published Books:

David J. Clark, WordStar Instant Reference (Sybex Prompter Series),
Sybex, 1988.

Tom Rugg and Werner Fiebel, WordStar Included, Bantam Computer Books,
1993

M. David Stone, Getting the Most from WordStar and MailMerge:
Things MicroPro Never Told You, Prentice-Hall,
1984

Users' Manuals:

MicroPro International Corporation, WordStar Professional, Release 5,
1988.

SoftKey International Inc., WordStar for Windows:
Word Processing and Precision Publishing All in One, 1994

Electronic Document:

WordStar International Incorporated,
File Format for WordStar Release 7.0,
March 17, 1992 (Retrieved from the internet, October 14, 1997 )
*/
/*-----*/

```